The cream of innovation, on your premises.

Practical

Quickream is the latest innovation from Elmeco, leading Italian manufacturer of premium frozen and cold-drink beverages dispensers. It has been created for preparation and serving of premium soft ice-cream product. Thank to the user-friendly electronic touchpad and patented dispensing system Quickream provides servings of approximately 70 grams (2.5 oz) each.

- Patented Total Cold refrigeration system keeps product at a constant temperature to the very last portion left in the machine
- The drive shaft of each Quickream unit which is manufactured with a Seal-Less patent, makes it uniquely the most hygienic & safest product of its kind on the market today
- User friendly digital touchpad incorporates: portion control mechanism temperature and density control system programmable auto-defrost timer
- Innovative removable external condenser air-filter makes the periodical maintenance a snap



With its compact dimensions, smooth design and bright colours, Quickream's panels give an operator plenty of space for PoS (Point of Sales) materials. Quick and easy to disassemble, the machine guarantees maximum hygiene for milk-based products.

A blend of design and technology will increase not only your profits but also enhance look of your premises.

Respect for the environment

Thank to the brushless drive system, dual-speed production process and standby temperature settings, Quickream reduces energy consumption and minimizes noise generated by internal components. In 90% Quickream is made with recyclable and reusable materials, which perfectly reflects Elmeco's dedication to protect natural environment.

Available in



GREY Pantone 4



PURPLE Pantone 279



LILAC Pantone



REEN Pantone 366





Technical specifications

MODELLO/MODEL	Quickream1
CAPACITÀ (LITRI)/LITRES	3-4 lt/0.79 gallon
PESO/WEIGHT	30 kg/65 lbs
DIMENSIONI/DIMENSION	depth: 471 mm/19" width: 276 mm/11" height: 712 mm/28"
POTENZA MACCHINA/ MACHINE POWER	420 watt
POTENZA COMPRESSORE/ COMPRESSOR POWER	300 watt 1/3 HP/2.6 Amps
VOLTAGGIO FREQUENZA/ VOLTAGE FREQUENCY	230 volts/50 hz 115 volts/60 hz

- Temperature control Range between -6°C/21°F and -8°C/17.5°F in increments of 0.5°C/0.875°F
- Shaker system Brushless low energy consumption
- Stand-by mixing velocity 50 Rpm
- Mixing velocity 70 Rpm





Elmeco srl Via Circumvallazione Esterna, 12 80025 Casandrino (NA) Tel: +39.081.5055724 Fax: +39.081.5055726 info@elmeco.com www.elmeco.com

Elmeco srl North & South Americas Subsidiary 4640 S. Carrollton Ave. Suizzte 200-8 New Orleans, LA 70119 - U.S.A. Tel: 1.877.4ELMECO (35.6326); +1.504.488.1060 Fax: +1.504.613.4603