

# ICE STORAGE EQUIPMENT 72" DOUBLE DOOR UPRIGHTS


## Common Features

- 1 1/2" foamed in-place polyurethane insulation
- Convenient snout door spring hinge
- S/S baffle behind door prevents ice overflow
- Clear polycarbonate sliding view windows
- Factory installed 1" IPS plastic drain
- FOB origin on all freight unless pre-approved arrangements are made on a per order basis

| Double Door Upright                                                                                                                                                                                                                                                                                                                                            |          |       |       |        |        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------|-------|--------|--------|
| Model                                                                                                                                                                                                                                                                                                                                                          | Capacity | Width | Depth | Height | Weight |
| 4325                                                                                                                                                                                                                                                                                                                                                           | 4839lbs  | 72"   | 48"   | 96"    | 980lbs |
| <ul style="list-style-type: none"> <li>• All stainless steel</li> <li>• Sleeves are W x D x 20"H and have a view window</li> <li>• Sleeves can be customized to add height, special doors and more</li> <li>• Sleeves are shipped separate</li> <li>• Ice maker's that weigh over 800lbs each may require additional reinforcement. Call for quote.</li> </ul> |          |       |       |        |        |

4325





# ICE STORAGE EQUIPMENT

---

## TECHNICAL PRODUCT DATA

### Part 1 – Uprights

#### 1.1 GENERAL

- A. Height includes 6" adjustable legs and 1" for top closures. Add 10 1/2" to depth after Install for snout/door assembly.
- B. Poly snout(s) and set(s) of sliding view windows are tool-free install.
- C. Dimensions shown in inches and pounds.
- D. Application capacity is determined as 90% of total volume in cubic feet x 34lb./ cu. ft. avg. Ice density. Shipping weights are approximate and variable.

#### 1.2 CLOSURES

- A. Equipped with a standard reinforced ABS top that will accommodate ice maker. Please call for special application requirements.
- B. Stainless steel closures are built to match ice manufacturing specification are included in price for all S/S lined bins (included in 705 and 905 models). Please specify ice maker to be used at time of order.
- C. S/S tops are fully gasketed, reinforced and cut to ice maker of choice.

#### 1.3 ADJUSTABLE FEET

All models equipped with adjustable bullet and/or flanged feet.





#### 1.4 MATERIALS

- A. Cabinets fabricated from T304 stainless steel sheet, (T316 stainless steel available at additional cost) conforming to ASTM A240. All exposed surfaces polished to a No. 4 brushed satin finish.
- B. SBB models have stainless steel fronts, sides, backs and bottoms.
- C. SS models have stainless steel fronts and sides with galvanized steel backs.
- D. Seamless molded polyethylene liners with 1 1/2" Foamed-in-place polyurethane insulation.
- E. Sliding view windows are 1/4" polycarbonate.



#### 1.5 PRISON PACKAGE OPTIONS

- A. Prison package/Anti-vandalism package (quotes available upon request).
- B. Both single and double door units are available with these options; either is available individually or as a package.
  - 1. 20 gauge stainless steel liner (either seamed or fully welded) (24 ga. Standard).
  - 2. All stainless steel snout with lockable door.
  - 3. Stainless steel top closure.
  - 4. 6" stainless steel bolt down flanged legs.
  - 5. Stainless steel view window cover plate with security screws for authorized removal.

***All ice storage bins and shuttle systems are available  
with a stainless steel liner, fully welded with coved  
corners. Please call for pricing!***



4325 UPRIGHT MODIFIED



UPRIGHT BIN

DATE: 01-03-07  
DRAWN BY: M.L.S.  
SCALE: AS NOTED  
DWG NO.  
4.345  
SHEET 1 OF 1