



JOB:
ITEM:
QTY:



“U” Type Nesting Racks

Virtually maintenance free, our racks are built for the long haul.

All welded construction insures the maximum strength and stability of each rack...Shipped assembled for immediate use. Supporting cross braces have gussets securely welded into place to prevent “racking”.

“Worry Free” Handling

Specially designed to hold trays by the bottom insuring equal load distribution for easy, “worry free” handling. Heavy duty aluminum tube and angle slides maximize strength and durability.

Easy to Maneuver

Equipped with four 5” heavy duty platform type casters, these all welded aluminum carts are built to be pushed around. Non-marking wheels protect floors and minimize noise.

Guaranteed To Last

Guaranteed to last, each rack carries a **Lifetime Guarantee** against rust and corrosion as well as a **Five-Year Guarantee** against material defects and workmanship.

Sanitary

Each unit is all welded with all seams fully welded and sealed providing a smooth, easy to clean surface. No cracks or crevices to trap dirt!



Model #1331U



Phone: 800-255-0104
Fax: 877-877-7687
www.newageindustrial.com
sales@newageindustrial.com

New Age Industrial reserves the right to modify or make changes at any time without notice to materials and specifications.

SPECIFICATIONS

MATERIAL: Hi-tensile, corrosion resistant, rust proof, primary extruded aluminum, Type 6463-T5 alloy.

CONSTRUCTION: All heli-arc welded with all seams welded and sealed (no rivets).

SIDES: Each side had two vertical posts of 1" x 1" x .070 wall tube. Welded to each side are angle runners of 1 1/4" x 1 5/8" x .100 wall aluminum angle, spaced on 2" or 3" centers.

HORIZONTAL "U" SUPPORTS: Three "U" support constructed of 1" x 2" tube, welded into a "U" shaped unit


CORNER GUSSETS: Gussets of 1 1/2" x 1 1/2" x 5/8" thick angle are welded to the inside angles (bottom side) where horizontal cross bracing meets vertical uprights.

Note: Each gusset requires 4-1/2" of weld.


BASE: A "U" support frame with pre-tapped plates welded to each corner.

CASTERS: Platform type, 5" diameter wheel, full swivel design with sealed ball bearing axle. Wheel material is non-marking polyurethane.

NSF Certified.



Model #1331U



Model No.	Size-W	Size-H	Size-D	Runner Spacing	Pan Cap.	Wt.
1330U	20 1/2"	69 3/4"	36"	5"	30	86#
1331U	20 1/2"	69 3/4"	36"	3"	20	72#

NEW AGE
INDUSTRIAL



Phone: 800-255-0104
 Fax: 877-877-7687
www.newageindustrial.com
sales@newageindustrial.com

New Age Industrial reserves the right to modify or make changes at any time without notice to materials and specifications.